

## FLEXCORE | Your benefits

### ADJUSTABLE FOR VARIOUS PIPING LAYOUTS

Extremely variable: Flexible to install due to 4 x 90° turnable suction and discharge flanges.

### ENORMOUS INCREASE OF LIFETIME

Optimized mechanical seals guarantee maximum lifetime. Due to a pre-assembled, easy-to-replace cartridge unit, downtimes are drastically reduced.

### HIGH PERFORMANCE FOR MAXIMUM SERVICE LIFE

Less wear due to hardened spindle set combined with patented balancing system.

### FULFILLS LATEST NORMS AND STANDARDS

- API 614 / 676 3<sup>rd</sup> edition
- Ship class type approvals
- ATEX conformity

## 24 MONTHS GUARANTEE

**Leistritz**  
PUMP TECHNOLOGY

**NEW**

**Leistritz**  
PUMP TECHNOLOGY



If you have any questions,  
please contact:  
**Philipp Rossow**  
T +49 (0)911 4306-634  
[prossow@leistritz.com](mailto:prossow@leistritz.com)



Further information:  
<https://pumps.leistritz.com/en/flexcore>

#### Subsidiaries:

Leistritz Italia srl., Milan  
Leistritz Advanced Technologies Corp., Allendale  
Leistritz Machinery (Taicang), Co., Ltd., Taicang  
Leistritz SEA, Pte. Ltd., Singapore  
Leistritz Middle East FZE, Sharjah  
Leistritz India Private Limited, Chennai



Leistritz Pumpen GmbH | Markgrafenstrasse 36-39 | 90459 Nuremberg  
T +49 911 4306-9650 | F +49 911 4306-490 | [flexcore@leistritz.com](mailto:flexcore@leistritz.com)

[pumps.leistritz.com](https://pumps.leistritz.com)

LP-27 en 11/19 500 fr



## INNOVATION

**FLEXCORE | 25**

**FLEXCORE | 32**




FLEXCORE | Facts

- 1 Steel casing, hardened spindle set
- 2 FLEXCORE cartridge unit
- 3 Flange connections: DIN, ASME or SAE
- 4 One pump casing for two different cartridge units (FLEXCORE 25 & FLEXCORE 32)



MADE IN GERMANY

2 FLEXCORE | CARTRIDGE UNIT




FLEXCORE | PERFORMANCE DATA

	FLEXCORE   25	FLEXCORE   32
Viscosity	1.1 cSt to 2,500 cSt	1.1 cSt to 2,500 cSt
Operating temperature	minus 10°C to 180°C	minus 10°C to 180°C
Flow rate	7 l/min - 50 l/min	15 l/min - 100 l/min
Suction pressure	max. 8 bar	max. 8 bar
Differential pressure	1 bar to 40 bar	1 bar to 40 bar
Size ø x l	140 mm x 416 mm	140 mm x 416 mm
Weight	28 kg	28 kg

← **UNIQUE PERFORMANCE!**  
Up to 10 bar differential pressure, even at viscosities of only 1.1 cSt.

FLEXCORE | VARIANTS: 4 x 90° turnable suction and discharge casing



FLEXCORE | 25  
FLEXCORE | 32  
Delivery from stock\*

- Additionally available from 2020:
- Cast casing
  - Further pump sizes
  - Retrofittable sensor packages for pump monitoring

\* Subject to prior sale